

Platform

- 1.16 m X 3.91 m platform
- 1.49 m manual roll-out deck extension
- Composite treated wooden floor
- Fold-down handrails
- Self-closing gate
- Removable platform console box
- Platform console function status LED's¹
- Lanyard attach points
- Proportional drive control
- Load sensing system
- Two speed drive selection

Power & Transmission

- 2 x 24V x 350 A/hr Gell traction cell batteries
- Removable battery/ electrical compartment hoods
- 220V, 50 amp automatic battery charger
- Hydraulic transmission
- Dual motor front wheel drive & steer
- Automatic dual wheel brakes
- Drive disconnect/brake release

¹ Indicator LED lights on platform control console for tilt, high drive, lift, drive and overload.

Functional Equipment & Accessories

- Steel mesh scissor guards
- Non marking solid tyres (639 x 220 x 480)
- 3 degree tilt indicator light with cut-out
- Ground control selector switch with key lock
- Full grease lubrication on all scissor arm bushings
- Scissor maintenance prop
- Manual descent system
- Battery condition indicator
- Hour meter
- Horn
- Lifting/tie down lugs

Available Options

- AC cable to platform
- Dual voltage (110/230V) 40amp automatic battery charger
- Travel alarm



JLG Industries Inc.
Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands
Tel: +31 (0)23 565 5665
Fax: +31 (0)23 557 2493
e-mail address: europe@jlg.com
www.jlgeurope.com
An Oshkosh Corporation Company

Printed in UK
FORM No.: DS008-
PART NO.: DS008-ENGLISH



153-12

| | |
|------------------------------------|---------------------------------------|
| A. Platform height – elevated | 15.30 m |
| B. Platform height – lowered | 2.10 m |
| C. Platform railing height | 1.10 m |
| D. Stowed height (rails folded) | 2.50 m |
| E. Platform size | 1.16 m x 3.91 m |
| F. Platform length fully extended | 5.40 m |
| G. Overall width | 1.22 m |
| H. Overall length | 4.12 m |
| I. Wheelbase | 2.90 m |
| Ground clearance | 0.11 m |
| Platform capacity | 500 kg |
| Capacity on deck extension | 500 kg |
| Lift/lower time | 70 / 50 sec. |
| Maximum drive height | 7.00 m |
| Maximum operational slope | 3 degrees |
| Machine weight ¹ | 7,300 kg |
| Maximum ground bearing pressure | 14.0 kg/cm ² |
| Drive speed – lowered | 2.5 km/h |
| Drive speed – elevated | 0.7 km/h |
| Gradeability | 15% |
| Turning radius – inside | 1.60 m |
| Turning radius – outside | 4.10 m |
| Tyres (solid rubber - non marking) | 639 x 220 x 480 |
| Brakes | Automatic – Front Hydraulic |
| Drive | Hydraulic |
| Batteries | 2 x 24V x 350 A/hr Gell Traction cell |
| Charger 220 V | 48V x 50 Amp Automatic |
| Charger 110 V/240 V | 48V x 40 Amp Automatic |
| Pump motor | 2 x 3.7 kW |
| Hydraulic system | 65 L |

¹ Certain options or country standards may increase weight and/or dimensions.

